

**SiT5302****High Frequency Stratum 3 MEMS VCTCXO**  
Advanced Information**■ Features, Benefits and Applications**

- Any frequency between 60.000001 and 220 MHz
- $\pm 4.6$  PPM total frequency stability over 20 years
- $< \pm 0.37$  PPM (370 PPB) 24-hour hold-over stability
- $\pm 0.1$  PPM (100 PPB) over-temperature stability (0 - 70°C).
- Excellent phase jitter: 0.5 ps (12 kHz to 20 MHz)
- Voltage control with  $\pm 12.5$  PPM pull range
- LVCMOS/HCMOS compatible output
- Three 4-pin packages: 3.2 x 2.5, 5.0 x 3.2, 7.0 x 5.0 (mmxmm)
- Contact SiTime for the following options:
  - SoftEdge™ Configurable rise/fall time control
  - Extended commercial and industrial temperature range options
  - Fixed frequency TCXO option
  - 2.5 x 2.0 footprint compatible package support
- Outstanding silicon reliability of 2 FIT (10x improvement over quartz-based devices)
- Ideal for telecom, networking, smart meter, and IP timing applications

**■ Specifications****Electrical Characteristics**

Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition
Output Frequency Range	f	60.000001	–	220	MHz	
Frequency Stability						
Overall stability	F_stab	-4.6	–	+4.6	PPM	Inclusive of temperature, 20 year aging, supply voltage and output load
Stability over temperature	F_temp	-0.10	–	+0.10	PPM	0 to 70 °C (Ordering code: Q)
		-0.20	–	+0.20	PPM	-20 to 70 °C (Ordering code: P)
Supply Voltage	F_vdd	-0.025	–	+0.025	PPM	$\pm 5\%$ Vdd
Output Load	F_load	-0.005	–	+0.005	PPM	$\pm 10\%$ of 15 pF load
24 hour hold-over stability	F_hold	-0.37	–	+0.37	PPM	Inclusive of temperature, 24 hour aging, supply voltage and output load
Initial Tolerance	F_init	-1	–	1	PPM	at 25°C
Operating Temperature Range	T_use	0	–	+70	°C	Commercial. Contact SiTime for extended commercial (-20 to 70 °C) or industrial temperature (-20 to 45°C) range support
Supply Voltage	Vdd	2.25	2.5	2.75	V	Any supply voltage between 2.5V and 3.3V is supported to 1 decimal of accuracy
		2.97	3.3	3.63	V	
Pull Range	PR	$\pm 12.5$			PPM	
Control Voltage	VC	10	–	90	%VDD	
Linearity	Lin	–	–	1	%	
Frequency Change Polarity	–	Positive slope			–	
Control Voltage -3dB Bandwidth	V_BW	–	–	8	kHz	
Current Consumption	Idd	–	33	35	mA	No load condition, f = 100MHz, Vdd = 2.5 V or 3.3 V
Duty Cycle	DC	45	–	55	%	All Vdds.
Rise/Fall Time	Tr, Tf	–	1.5	2	ns	15 pF load, 10% - 90% Vdd
Output Voltage High	VOH	90%	–	–	Vdd	IOH = 7mA, Vdd = 3.3V IOH = 4.5mA, Vdd = 2.5V
Output Voltage Low	VOL	–	–	10%	Vdd	IOL = 7mA, Vdd = 3.3V IOL = 4.5mA, Vdd = 2.5V
Output Load	Load	–	–	15	pF	At maximum frequency and supply voltage. Contact SiTime for higher output load options
Startup Time	T_start	–	–	10	ms	Measured from the time Vdd reaches its rated minimum value
RMS Period Jitter	T_jitt	–	1.7	2.5	ps	f = 100 MHz, Integration bandwidth = 12 kHz to 20MHz,
RMS Phase Jitter (random)	T_phj	–	0.5	–	ps	f = 100 MHz, Integration bandwidth = 12 kHz to 20MHz, all Vdds

**SiT5302****High Frequency Stratum 3 MEMS VCTCXO**  
Advanced Information**SiTime™****Specifications (Cont.)****Pin Description Tables**

Pin #1 Functionality
VIN
0 - Vdd: produces voltage dependent frequency change

Pin Map	
Pin	Connection
1	VC
2	GND
3	CLK
4	VDD


**Absolute Maximum Ratings**

Attempted operation outside the absolute maximum ratings of the part may cause permanent damage to the part. Actual performance of the IC is only guaranteed within the operational specifications, not at absolute maximum ratings.

Parameter	Min.	Max.	Unit
Storage Temperature	-65	150	°C
VDD	-0.5	4	V
Electrostatic Discharge (Human Body Model)	-	2000	V
Soldering Temperature (follow standard Pb free soldering guidelines)	-	260	°C
Number of Program Writes	-	1	NA
Program Retention over -40 to 125°C, Process, VDD (0 to 3.65 V)	1,000+	-	years

**Environmental Compliance**

Parameter	Condition/Test Method
Mechanical Shock	MIL-STD-883F, Method 2002
Mechanical Vibration	MIL-STD-883F, Method 2007
Temperature Cycle	JESD22, Method A104
Solderability	MIL-STD-883F, Method 2003
Moisture Sensitivity Level (MSL)	MSL1 @ 260°C

**Phase Noise Plot<sup>[1]</sup>****Note:**

1. The maximum offset frequency is half of the clock (or carrier) frequency for a digital clock.

# SiT5302

## High Frequency Stratum 3 MEMS VCTCXO Advanced Information




### ■ Dimensions and Land Patterns

Package Size – Dimensions (Unit: mm) <sup>[2]</sup>	Recommended Land Pattern (Unit: mm) <sup>[3]</sup>
<p><b>3.2 x 2.5 x 0.75 mm</b></p>	
<p><b>5.0 x 3.2 x 0.75 mm</b></p>	
<p><b>7.0 x 5.0 x 0.90 mm</b></p>	

**Notes:**

- Top marking: Y denotes manufacturing origin and XXXX denotes manufacturing lot number. The value of "Y" will depend on the assembly location of the device
- Refer to application note AN10002 for recommended RLL to power supply bypass for better supply noise immunity.

**SiT5302****High Frequency Stratum 3 MEMS VCTCXO**  
Advanced Information**SiTime™****Part No. Guide - How to Order****Notes:**

4. Contact SiTime for SoftEdge™ output waveform that reduces EMI and is similar to clipped sinewave in functionality.

**Frequency Stability vs. Temperature Range Options<sup>[5]</sup>**

Frequency Stability Over-temperature (PPM)	Temperature Range (°C)	Supply Voltage	
		2.5 V	3.3 V
$\pm 0.1$	0 to +70	✓	✓
	-20 to +70	Contact SiTime	
$\pm 0.2$	0 to +70	✓	✓
	-20 to +70	Contact SiTime	

5. Contact SiTime for wider operating temperature range support.

© SiTime Corporation 2011. The information contained herein is subject to change at any time without notice. SiTime assumes no responsibility or liability for any loss, damage or defect of a Product which is caused in whole or in part by (i) use of any circuitry other than circuitry embodied in a SiTime product, (ii) misuse or abuse including static discharge, neglect or accident, (iii) unauthorized modification or repairs which have been soldered or altered during assembly and are not capable of being tested by SiTime under its normal test conditions, or (iv) improper installation, storage, handling, warehousing or transportation, or (v) being subjected to unusual physical, thermal, or electrical stress.

**Disclaimer:** SiTime makes no warranty of any kind, express or implied, with regard to this material, and specifically disclaims any and all express or implied warranties, either in fact or by operation of law, statutory or otherwise, including the implied warranties of merchantability and fitness for use or a particular purpose, and any implied warranty arising from course of dealing or usage of trade, as well as any common-law duties relating to accuracy or lack of negligence, with respect to this material, any sitime product and any product documentation. products sold by sitime are not suitable or intended to be used in a life support application or component, to operate nuclear facilities, or in other mission critical applications where human life may be involved or at stake. all sales are made conditioned upon compliance with the critical uses policy set forth below.

**CRITICAL USE EXCLUSION POLICY**

BUYER AGREES NOT TO USE SITIME'S PRODUCTS FOR ANY APPLICATION OR IN ANY COMPONENTS USED IN LIFE SUPPORT DEVICES OR TO OPERATE NUCLEAR FACILITIES OR FOR USE IN OTHER MISSION-CRITICAL APPLICATIONS OR COMPONENTS WHERE HUMAN LIFE OR PROPERTY MAY BE AT STAKE.

SiTime owns all rights, title and interest to the intellectual property related to SiTime's products, including any software, firmware, copyright, patent, or trademark. The sale of SiTime products does not convey or imply any license under patent or other rights. SiTime retains the copyright and trademark rights in all documents, catalogs and plans supplied pursuant to or ancillary to the sale of products or services by SiTime. Unless otherwise agreed to in writing by SiTime, any reproduction, modification, translation, compilation, or representation of this material shall be strictly prohibited.