

Crystal Unit

YSX321SL




Applications

- Smart Wearable
- IOT Communication

Features

- Dimensions: 3.20 x 2.50 x 0.70 mm..
- Standard Frequency: 8~64MHz

- High precision and high frequency stability.
- Extremely good for reducing EMI effect.



Specifications (规格参数)

| Item | Symbol | Specifications |
|--|--------|-----------------------------|
| Nominal Frequency Range (额定频率范围) | f_nom | 8~64MHz |
| Vibration Mode (震动模式) | - | AT Fundamental |
| Load Capacitance (负载电容) | CL | 10pF, 20pF, or specify |
| Frequency Tolerance (频率偏差) (at 25°C) | f_tol | ±10ppm, ±20ppm, or specify |
| Frequency Versus Temperature Characteristics (频率-温度特性) | f_tem | ±20ppm, or specify |
| Operating Temperature (工作温度) | T_use | -40~+85°C or specify |
| Storage Temperature (储存温度) | T_stg | -55~+125°C |
| Shunt Capacitance (静态电容) | C0 | 7pF Max. |
| Level of Drive (激励电平) | DL | 1~200µW Max.(100µW typical) |
| Aging (老化) (at 25°C) | f_age | ±3ppm/year Max. |

Equivalent Series Resistance (等效串联电阻(ESR))

| YSX321SL | |
|----------------|------------|
| 8 ~ 11.2892MHz | 150 Ω Max. |
| 12 ~ 16MHz | 80 Ω Max. |
| 17 ~ 64MHz | 50 Ω Max. |

Dimensions and Recommended land pattern (外观尺寸及推荐焊盘)

| Dimensions (Unit: mm) | Recommended land pattern(Unit: mm) |
|---|---|
| <p>Top View</p> <p>Side View</p> <p>Bottom View</p> | <p>Top View Crystal Connection</p> <p>Top View Suggested Layout</p> |